


CAVIBLASTER DIESEL ENGINE 2570-D





This is an industrial workhorse which generates a super stream of high velocity cavitation

for high efficient cleaning, it can strip fouling and corrosion to bare metal if desired

This unit is capable of achieving surface preparation stage Sa.2.5

Accessories Included:

Feed Hose (15 feet), By-Pass Hose (15 feet),

High Pressure Hose (50 feet), Zero-Thrust Balanced Gun, Battery Start

Optional Accessories:

Aditional pressure hose available in 50 ft or 100 ft sections Max. Pressure hose length recommended up to 300 ft (100 meters) total























CAVIBLASTER DIESEL ENGINE 2570-D





SKID Dimensions	
Height	63" / 160 cm
Width	57" / 145 cm
Length	97" / 247 cm
Weight (max w/fuel)	5,500 lbs. / 2,500 kg
Fuel/Oil Containment Pan	Yes
Lifting Eyes / Fork Slots	Yes

Pump System	
Pressure Pump	HPP H-15 0/3 SAP
Туре	Po sitive Displacement
Flow Rate	29 GPM / 110 L/min
Noz zle Pressu re	7,200 psi /500 Bar
Hose Diam/Max. Length	3/4" / 600 Lft - 19 mm / 200 m

Feed System	
Feed Pump	Centrifugal Self-Prime
Flow Rate	80 GPM/3 04 L/min
Lift	20Ft / 6 m
Power transm.	Belt

Drive System	
Driver	John Deere, Tier 3
Engine Type	4-Cylinder - 4-Cycle
Co olin g System	Liquid
Combustion System	Turbo charge
AirIntake	TCA
Output Max HP/kW	173 / 129 @ 2400rpm
Transmission	BELT Drive PTO
Start in g System	Electric Starter
Emergency Shut-off	Electric

Tools		
Tool Type	Zero-Thrust Balanced Dump-Gun	

Shipping Dimensions	
Pallet 58x 98x 70 "	6,000 Lbs Gross weight











SYNERGY INFRASTRUCTURE





CAVIBLASTER DIESEL ENGINE 2570-D

Contact us

P.O. Box – 237849, Warehouse No 8, Al Maidoor Warehouse, Al Qusais, Industrial Area - Dubai - UAE

Website: www.synergyequipment.comEmail: ram@synergyequipment.comFor Sale: info@synergyequipment.com













